BL/TZ INFORMATION

No. 2019-0141 2019/5/29 Blitz Co., Ltd.

Additional Applications



Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit.

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(MSRP w/tax)	(MSRP)	(Code No.)	(JAN Code)
MITSUBISHI							
DELICA D:5							
DELICA D:5	19/02-	CV1W	4N14	¥172,800	¥160,000	92479	4959094924791
URBAN GEAR							







Front :-62mm Down / Rear :-66mm Down

Product Specification					
	Front	Rear			
Damping Force Adjustability	32 Levels	32 Levels			
Length Adjustment	0	0			
Shock Absorber Structure	Coilovers	Separate			
Upright or Inverted	Upright	Upright			
Hamau Mariat	Reinforced	Stock			
Upper Mount	Rubber				
Height Adjustment	6.0	8.0			
Ride Height Adjustability mm	220	230			
Remarks	ST	BS			
Damping Force Adjustability	-100 ~ 0	-100 ~ -45			
Length Adjustment	-	_			

**Abbreviation for Spring Types \[\subseteq ST: ID62 \] Straight Spring J, \[\subseteq BS: Barrel or Tapered, Vehicle Specific Springs J \] **Adjustability in ride height may vary between vehicles.

BL/TZ INFORMATION

Information on Verification Test Vehicle

This product has been tested on the following vehicle.

Data taken from in house measurements.

Measurements for the vehicle height may differ depending on the vehicle's grade and options.

The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle.

Please use the following data as a reference and adjust your vehicle height accordingly.

	確認車両データ				
	(Information on Verification Test Vehic	cle)			
車名/型式/グレード (Vehicle Name/Model/Grade)	DELICA D:5 URBAN GEAR / CV	/1W / G-Power Package			
	フロント (Front)	リア (Rear)			
車 重[kg] (Vehicle Weight)	1090	860			
レバー比 (Lever Ratio)	1.0	ショック: 0.9 スプリング: 1.5 (Shock Absorber) (Spring)			
タイヤサイズ (Tire Size)	225/55/18	225/55/18			
ホイールサイズ (Wheel Size)	18インチ × 7.0J インセット 38 (INCHES) (INSET)	18インチ × 7.0J インセット 38 (INCHES) (INSET)			
		グデータ g Data)			
スプリングバネレート(kgf/mm) (Spring Rate)	6.0	8.0			
スプリング自由長[mm] (Free Length of Spring)	220 230				
スプリング内径【】は外径 (Spring Inner Diameter【Outer】)	φ 62	φ 80 – φ 84			
	アライメントデータ (Alignment Data)				
トー 〔純正値〕 (Toe [Stock Measurements])	0° 08' [1.0 ± 2.0mm]	+0° 02' (3.0 ± 2.0mm)			
キャンバー 〔純正値〕 (Camber [Stock Measurements])	-2° 09' [0° 15' ± ° 30']	-2° 09' [-0° 10' \pm 0° 30']			
キャスター 〔純正値〕 (Caster 〔Stock Measurements〕)	2° 20' [2° 25' ± 0° 30']	-			
	車高データ (Vehicle Height Data)				
地面~フェンダー[mm] (Ground~Fender [mm])	743	748			
純正からのダウン量[mm] (Difference from Stock [mm])	-62	-66			
車高調整範囲[mm] (Ride Height Adjustability [mm])	−100 ~ 0	-100 ~ -45			
	減衰力データ (Damping Force Data)				
開発時減衰力 (Damping Force during Development)	20	16			

■Precautions During Installation

• Ride height adjustability has been taken from Urban Gear.

■ Other Remarks

- Compatibility has been tested on models made after February 2019.
- Ornering performance is enhanced by limiting vehicle roll.
- Lower your vehicle for a stylish form.
- Change the damping force depending on the number of passengers to achieve optimum comfort.