


Additional applications for the DAMPER ZZ-R SpecDSC Plus has been confirmed for the HONDA CIVIC (FL4)







Front: -45mm Down / Rear: -47mm Down

Click here for further information on DAMPER ZZ-R Spec DSC PLUS

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(Code No.)	(JAN Code)
HONDA					
CIVIC	2022/07-	FL4	LFC	98585	4959094985853

Product Description

- Industry first Full Auto Mode is able to automatically adjust the damping force depending on how the vehicle's balance changes depending on variables such as road condition and number of passengers.
- The UP/Down switch has been enlarged and an additional rotary switch has been employed to make complex operations easier.
- The damping force can be easily adjusted from a controller inside your vehicle (Choose from 96/64/32 levels of adjustment). By utilizing a stepping motor, a maximum of 96 levels of adjustment is possible to finely tune the vehicle setup for your desired ride quality.
- During map control mode, variables such as rotational G, acceleration G, and vehicle speed are taken into account when automatically adjusting the damping force. G can be displayed in real time and its peak value can be shown as well.
- Total of 22 presets can be saved. The ADVANCED mode allows complex and detailed management of the damping force.
- With the separately sold GPS sensor kit, the vehicle speed can be easily inputted.

Product Specification				
	Front	Rear		
Length Adjustment	0	0		
Shock Absorber Structure	Coilovers	Separate		
Upright or Inverted	Upright	Upright		
Upper Mount	Stock	Reinforced Rubber		
Spring Rate kgf/mm	6.0	5.0		
Free Length of Spring mm	180	190		
Spring Type※	BS	BS		
Ride Height Adjustability mm	- 75 ∼ 0	-65 \sim -25		



■ Remarks : Rear damping force adjustment located inside the wheel well.

*Abbreviation for Spring Types \[ST: ID62 Straight Spring \], \[FBS: Barrel or Tapered, Vehicle Specific Springs \] XAdjustability in ride height may vary between vehicles.

Optional Parts			
Product Name	Code No.	Remarks	
DSC PLUS Vehicle Specific Set TYPE-A	15236	Upgrade to the DSC Plus with the vehicle specific set	
DSC PLUS GPS Sensor Kit	15214	Vehicle speed can be easily inputted	
DSC PLUS Remote Switch	15219	Allows you to conveniently switch settings.	

DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー	車名	型式	年式	グレード
(Manufacturer)	(Vehicle Name)	(Model)	(Model Year)	(Grade)
HONDA	CIVIC	FL4	2022年7月	e:HEV

確認車両情報		フロント (Front)	リア (Rear)	備考 (Remarks)
	車重(kg) (Vehicle Weight)	1630		
車両情報 (Vehicle Information)	軸重(kg) (Axle Weight)	920	710	
	タイヤサイズ (Tire Size)	235/40 R18	235/40 R18	
	ホイールサイズ (Wheel Size)	18inch 8.0J Inset50	18inch 8.0J Inset50	
	レバー比 (Lever Ratio)	1.0	1.1	
	├─ (Toe)	-0°04'	+0°09'	
アライメントデータ (Alignment Data)	キャンバー (Camber)	-0°13'	-2°21'	
	キャスター (Caster)	+5°40'	_	

DAMPER ZZ-R Spec	c .	フロント (Front)	リア (Rear)	備考 (Remarks)
	スプリングレート(kgf/mm) (Spring Rate)	6.0	5.0	
	スプリング自由長(mm) (Free Length of Spring)	180	190	
	スプリング内径(mm) (Spring Inner Diameter)	φ104.5 - φ62.5	φ62 - (φ115) - φ62	
	減衰力調整段数 (Damping force Adjustment)	1~32段	1~32段	
DAMPER ZZ-R 仕様(Spec.)	テスト時減衰力 (Tested Damping force)	16段	16段	DSC Plus装着時 32,64,96段へ変更可能
	地面〜フェンダー(mm) (Ground〜Fender)	637	639	
	基準車高(mm) (Difference from Stock)	-45	-47	
	車高調整範囲(mm) (Height Adjustment Range)	-75 ∼ 0	-65 ∼ -25	
	最低地上高(mm) (Minimum Ground Clearance)	95mm (アンダーパネル)		

Product Description

- Body roll has been limited for improved cornering performance.
- The suspension has been made to allow sufficient bump and rebound stroke for optimal ride comfort.
- Lower your vehicle for a stylish look.
- Make adjustments to the damping force to optimize ride quality depending on number of passenger and road condition.
- By installing the optimal DSC PLUS, the damping force can be controlled form inside the vehicle.