

Additional application for the DAMPER ZZ-R Lift Up version has been confirmed for the TOYOTA LANDCRUISER (FJA300W/VJA300W)

DAMPER ZZ-R LIFT UP

Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit

Click here for further details on DAMPER ZZ-R





(Vehicle)	(Model Year)	(Model)	(Engine Model)	(Code No.)	(JAN Code)
TOYOTA					
LANDCRUISER	2021/08-	FJA300W, VJA300W	F33A-FTV, V35A-FTS	92590	4959094925903

Product Description

Click here for price and availability

- Mono-tube adjustable coil over suspension kit.
- Employs 32 levels of damping force adjustability.
- Compatible with a wide range a circumstance from the street to the circuit.
- Aluminum upper mount, lock seat, and brackets have been utilized to maximize strength while minimizing weight.
- φ44 Mono-tube structure allows a fine balance of structural rigidity and smooth ride quality.

Product Specification					
	Front	Rear			
Damping Force Adjustability	32 Levels	32 Levels			
Length Adjustment	0	0			
Shock Absorber Structure	Coilovers	Separate			
Upright or Inverted	Upright	Upright			
Upper Mount	Reinforced Rubber	Stock			
Spring Rate kgf/mm	14.0	4.5			
Free Length of Spring mm	280	330/345			
Spring Type※	ST	BS			
Ride Height Adjustability mm	+10 ~ +60	+40 ∼ +80			



■ Remarks: Lift up version. Compatible with Gasoline, Diesel, all grades. Front and rear damping force adjustment dial located inside the wheel well.

Ride height data from FJA300W (ZX Grade)

**Abbreviation for Spring Types \[ST: ID62 Straight Spring \], \[\text{BS: Barrel or Tapered, Vehicle Specific Springs } \] \[\text{Adjustability in ride height may vary between vehicles.} \]

Optional Parts					
Product Name	Code	Remarks			
Vehicle Specific Set TYPE-U	15054	Upgrade to the DSC Plus with the vehicle specific set			

DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー	車名	型式	年式	グレード
(Manufacturer)	(Vehicle Name)	(Model)	(Model Year)	(Grade)
TOYOTA	LANDCRUISER	FJA300W	2023年5月	ZX

確認車両情報		フロント (Front)	リア (Rear)	備考 (Remarks)
	車重(kg) (Vehicle Weight)	2570		
	軸重(kg) (Axle Weight)	1430	1140	
車両情報 (Vehicle Information)	タイヤサイズ (Tire Size)	265/55 R20	265/55 R20	
	ホイールサイズ (Wheel Size)	20inch 8.0J Inset60	20inch 8.0J Inset60	
	レバー比 (Lever Ratio)	1.1	1.1	
	├- (Toe)	+0°01'	+0°16'	
アライメントデータ (Alignment Data)	キャンバー (Camber)	+0°45'	-0°04'	
	キャスター (Caster)	+2°45'	-	

DAMPER ZZ-R Spec.		フロント (Front)	リア (Rear)	備考 (Remarks)
	スプリングレート(kgf/mm) (Spring Rate)	14.0	4.5	(Herrista)
	スプリング自由長(mm) (Free Length of Spring)	280	330/345	
	スプリング内径(mm) (Spring Inner Diameter)	φ62	φ135 - (φ172) - φ100.5	
	減衰力調整段数	1段 ~ 32段	1段 ~ 32段	DSC Plus装着時
DAMPER ZZ-R 仕様(Spec.)	(Damping force Adjustment)	(HARD) (SOFT)	(HARD) (SOFT)	32,64,96段へ変更可能
	地面〜フェンダー(mm) (Ground〜Fender)	935	964	
	基準車高(mm) (Difference from Stock)	+52	+44	
	車高調整範囲(㎜) (Height Adjustment Range)	10 ~ 60	40 ~ 80	
	最低地上高(mm) (Minimum Ground Clearance)	224mm (アンダーパネル右側)		

初めてご使用される際の推奨減衰力	1.C.F.\\	2.4 <i>E</i> D	左記に記載の減衰に合わせ
(Recommended Damping force)	16段	24段	てからご使用ください

[%]Product shipped at damping force of 16. Turn the dial all the way to the right for level 1 which is the hardest.
%During installation turn the dial all the way to the right and then make adjustment towards the left accordingly.

Product Description

- Lift up version damper ZZ-R
- New setting for LAND CRSUIER ZX grade.
- As stock, the vehicle has a lower front end. The suspension balances the front and rear ride height to be more even
- Increase the ride height for a more aggressive look.
- Spring rate and shock length have been revised to allow greater height adjustability.
- Even while increasing the height, vehicle stability during high speed is maintained.
- Compatible with DSC PLUS. Change the damping force depending on the number of passenger for optimal comfort.
- By installing the optimal DSC PLUS, the damping force can be controlled form inside the vehicle.