

Additional application for the 「DAMPER ZZ-R L」 is now available for the LEXUS LM (TAWH15W)

DAMPER ZZ-R L

Adjustable suspension kit with springs and bump rubbers tailored vehicle specifically. Stock upper mounts are utilized and the amount of oil optimized for a smoother ride quality.

[Click here for more information on DAMPER ZZ-R L](#)



Front : 16mm Down / Rear : 26mm Down

(Vehicle)	(Model Year)	(Model)	(E/G Model)	(Code No.)	(JAN Code)
LEXUS					
LM	2023/12-	TAWH15W	T24A-1ZM-1YM	92657	4959094926573

[Click here for price and availability](#)

Product Characteristics

- The ZZ-R L series pursues greater quality, ride comfort and quietness compared to its predecessor.
- Employs 32 levels of damping force adjustability and height adjustable suspension kit.
- Balances comfort and stability at high speeds while moderately lowering the vehicle for style.
- To ensure optimal ride quality stock upper mount along with vehicle specific spring, and bump rubber are utilized. Furthermore, the amount of oil in the shock absorber has been optimized to ensure sufficient stroke length.
- φ44 Mono-tube structure allows a fine balance of structural rigidity and smooth ride quality.

Product Specification		
	Front	Rear
Damping Force Adjustability	32 Levels	32 Levels
Length Adjustment	○	○
Shock Absorber Structure	Coilovers	Separate
Upright or Inverted	Upright	Upright
Upper Mount	Stock	Reinforced Rubber
Spring Rate kgf/mm	7.5	10.5
Free Length of Spring mm	250	240
Spring Type※	BS	BS
Ride Height Adjustability mm	-30 ~ 0	-35 ~ 0



※Stock parts are not included

- Remarks : EXECUTIVE/Version L Compatible. Rear damping force dials located inside wheel well.
Ride height data from LM500h (6 passenger Version L).

※Abbreviation for Spring Types 「ST : ID62 Straight Spring」, 「BS : Barrel or Tapered, Vehicle Specific Springs」

※Adjustability in ride height may vary between vehicles.

DAMPER ZZ-R L Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー (Manufacturer)	車名 (Vehicle Name)	型式 (Model)	年式 (Model Year)	グレード (Grade)
LEXUS	LM500h	TAWH15W	2024年6月	Version L

確認車両情報		フロント (Front)	リア (Rear)	備考 (Remarks)
車両情報 (Vehicle Information)	車重(kg) (Vehicle Weight)	2440		
	軸重(kg) (Axle Weight)	1280	1160	
	タイヤサイズ (Tire Size)	225/55 R19	225/55 R19	
	ホイールサイズ (Wheel Size)	19inch 7.0J Inset35	19inch 7.0J Inset35	
	レバー比 (Lever Ratio)	1.0	1.2	
アライメントデータ (Alignment Data)	トー (Toe)	+0°03'	+0°05'	
	キャンバー (Camber)	-1°25'	-1°50'	
	キャスター (Caster)	+5°31'	-	

DAMPER ZZ-R L Spec.		フロント (Front)	リア (Rear)	備考 (Remarks)
DAMPER ZZ-R 仕様(Spec.)	スプリングレート(kgf/mm) (Spring Rate)	7.5	10.5	
	スプリング自由長(mm) (Free Length of Spring)	250	240	
	スプリング内径(mm) (Spring Inner Diameter)	φ107.5 - (φ175) - φ62.5	φ91.5 - (φ152) - φ78.5	
	減衰力調整段数 (Damping force Adjustment)	1段 ~ 32段 (HARD) (SOFT)	1段 ~ 32段 (HARD) (SOFT)	DSC Plus装着時 32,64,96段へ変更可能
	地面〜フェンダー(mm) (Ground~Fender)	751	752	
	基準車高(mm) (Difference from Stock)	-16	-26	
	車高調整範囲(mm) (Height Adjustment Range)	-30 ~ 0	-35 ~ 0	
	最低地上高(mm) (Minimum Ground Clearance)	112mm (マフラーパイプ(フレンジ後ろ))		※ホイールベース3000mmの為、 最低地上高100mm以上

初めてご使用される際の推奨減衰力 (Recommended Damping force)	16段	16段	左記に記載の減衰に合わせて からご使用ください
-------------------------------------------------	-----	-----	----------------------------

※Product shipped at damping force of 16. Turn the dial all the way to the right for level 1 which is the hardest.

※During installation turn the dial all the way to the right and then make adjustment towards the left accordingly.

Product Description

- Luxury model suspensions aimed for enhanced comfort and ride quality.
- For customer pursuing premium feel with outstanding driving performance that is expected from the Damper ZZ-R Series.
From cities to the highway unnecessary pitch and roll are suppressed for stability in all situations.
- Moderate lowering amount to achieve style that is distinct from the stock appearance.
- Bump rubbers and shock absorbers for both front and rear are specifically designed for the Damper ZZ-R L series.
- The kit also includes short bump rubbers for the rear springs.
- By installing the Optional Damper ZZ-R L Spec DSC PLUS, the damping force can be adjusted from inside the vehicle.
Additionally, G sensor and speed can be inputted for automated changes to the damping force.