


Additional application for the DAMPER ZZ-R has been confirmed for the HONDA CIVIC TYPE-R (FK8/FL5)

DAMPER ZZ-R

Suspension Kit equipped with Full Length Adjustability and 32 Levels of Damping Force Adjustments. Wide range adjustability can finely balance driving performance and ride quality to meet your needs from the street to the circuit

Click here for further details on DAMPER ZZ-R





(Vehicle)	(Model Year)	(Model)	(Engine Model)	(Code No.)	(JAN Code)
HONDA					
CIVIC TYPE-R	2017/09-2022/09	FK8	K20C	92648	4959094926481
	2022/09-	FL5	KZUC	92040	4939094920481

Product Description

- Mono-tube adjustable coil over suspension kit.
- Employs 32 levels of damping force adjustability.
- Compatible with a wide range a circumstance from the street to the circuit.
- Aluminum upper mount, lock seat, and brackets have been utilized to maximize strength while minimizing weight.
- φ44 Mono-tube structure allows a fine balance of structural rigidity and smooth ride quality.

Product Specification				
	Front	Rear		
Damping Force Adjustability	32 Levels	32 Levels		
Length Adjustment	0	0		
Shock Absorber Structure	Coilovers	Separate		
Upright or Inverted	Upright	Upright		
Upper Mount	Adjustable Pillow Ball	Reinforced Rubber		
Spring Rate kgf/mm	6.0	5.0		
Free Length of Spring mm	190	200		
Spring Type※	BS	BS		
Ride Height Adjustability mm	-45 ∼ 0	-45 ∼ -5		



Click here for price and availability

■ Remarks: Canceller included. Can be installed on vehicles equipped with Variable Damper System. However, the function will become unusable. Rear damping force dials located inside wheel well. Date from FL5.

**Abbreviation for Spring Types 「ST: ID62 Straight Spring」, 「BS: Barrel or Tapered, Vehicle Specific Springs」 XAdjustability in ride height may vary between vehicles.

Optional Parts				
Product Name Code No.		Remarks		
DSC PLUS Vehicle Specific Set TYPE-E	15240	Upgrade to the DSC Plus with the vehicle specific set		

DAMPER ZZ-R Spec & Vehicle Information



Data taken from in house measurements. Measurements for the vehicle height may differ depending on the vehicle's grade and options. The distance from the ground to fender may differ even when your vehicle is set at the same measurements as the test vehicle. Please use the following data as a reference and adjust your vehicle height accordingly.

メーカー	車名	型式	年式	グレード
(Manufacturer)	(Vehicle Name)	(Model)	(Model Year)	(Grade)
HONDA	CIVIC TYPE-R	FL5	2023年3月	TYPE-R

確認車両情報		フロント (Front)	ין (Rear)	備考 (Remarks)
	車重(kg) (Vehicle Weight)	1430		
	軸重(kg) (Axle Weight)	890	540	
車両情報 (Vehicle Information)	タイヤサイズ (Tire Size)	265/35R18	265/35R18	
	ホイールサイズ (Wheel Size)	18inch 9.5J Inset45	18inch 9.5J Inset45	
	レバー比 (Lever Ratio)	1.0	1.1	
	├– (Toe)	+0°02'	+0°04'	
アライメントデータ (Alignment Data)	キャンバー (Camber)	-2°13'	-2°37'	
	キャスター (Caster)	+7°23'	-	

DAMPER ZZ-R Spec.		フロント (Front)	リア (Rear)	備考 (Remarks)
	スプリングレート(kgf/mm) (Spring Rate)	6.0	5.0	,
	スプリング自由長(mm) (Free Length of Spring)	190	200	
	スプリング内径(mm) (Spring Inner Diameter)	Ф62 -(Ф115)- Ф62	Ф62 -(Ф115)- Ф62	
	減衰力調整段数	1段 ~ 32段	1段 ~ 32段	DSC Plus装着時
DAMPER ZZ-R	(Damping force Adjustment)	(HARD) (SOFT)	(HARD) (SOFT)	32,64,96段へ変更可能
仕様(Spec.)	地面〜フェンダー(mm) (Ground〜Fender)	651	652	
	基準車高(mm) (Difference from Stock)	-22	-21	
	車高調整範囲(mm) (Height Adjustment Range)	-45 ∼ 0	-45 ∼ -5	
	最低地上高(㎜) (Minimum Ground Clearance)	96mm (アンダーパネル(アルミ))		

初めてご使用される際の推奨減衰力	20段	24段	左記に記載の減衰に合わせ
(Recommended Damping force)	20 F X	Z4FX	てからご使用ください

[%]Product shipped at damping force of 16. Turn the dial all the way to the right for level 1 which is the hardest. %During installation turn the dial all the way to the right and then make adjustment towards the left accordingly.

Product Description

- Spring rate and damping force has been updated for a more comfortable ride quality.
- Front pillow ball upper mount allows adjustments to be made to the camber angle.
- By changing the damping force, the suspensions can handle different situation from the street to the circuit.
- SUSPENSION WARNING CANCELLER specifically for the Type R is included.
 - $\mbox{\em \%}$ The canceller makes sure an error will not show for the variable damper system.
 - **This does not complete remove the error inside the variable damper control unit.
- By installing the Optional DSC PLUS, the damping force can be adjusted from inside the vehicle.

 Additionally, G sensor and speed can be inputted for automated changes to the damping force.